

# GEOGARD Primer

## GEOGARD PRIMER

### Product Advantages

- Geogard Primer revitalises and conditions weathered urethane coatings prior to reapplication.

## PRODUCT INFORMATION

### DESCRIPTION

Geogard Primer is a single component industrial maintenance product utilised to enhance the adhesion of Geogard products.

### USAGE/PURPOSE

Geogard Primer is designed to promote adhesion of new Geogard products to weathered or aged Geogard products.

### LIMITATIONS

- Application temperature shall be above 4°C.
- Do not apply over tar or silicone based products.
- Do not apply over damp surfaces or when rain is imminent.

### PACK SIZE

3.78L  
18.9L

### PRODUCT CODE

700025  
700026

## TECHNICAL INFORMATION

Physical Properties	Test Method	Result
Weight per Gallon	ASTM D1475	7.5 lbs.
Solids by Weight		12% ± 1%
Viscosity @ 25°C	ASTM D562	24-32 CPS
Dry Time		30 minutes
Flashpoint	ASTM D3278	26°C
VOC		727g/L

## USAGE GUIDELINES

### PREPARATION

All surfaces are to be free of dirt, grease, oil, chalk, loose paint, rust, mortar and other foreign matter, which could prevent proper adhesion. This is best accomplished by power washing or utilising a stiff broom. All surfaces must be completely dry prior to the application of Geogard Primer.

### APPLICATION

Geogard Primer may be applied by brush, roller or spray. Allow to cure approximately 30 minutes or until material is dry and tacky. Geogard Primer must be top coated before it has cured hard. If material is allowed to dry completely, it will be necessary to apply an additional coat. The condition of the primer must be in a TNT State - Tacky Not Transfer.

Refer to appropriate application specification for further information.

## COVERAGE RATE - MINIMUM REQUIREMENTS

Wet mm	m <sup>2</sup> /L	3.78L	18.9L
0.101	9.83	37.10	185.70

\* ALL COVERAGE RATES ARE APPROXIMATE & VARY WITH SUBSTRATE CONDITION

## CLEAN UP

Xylene.

## HEALTH & SAFETY PRECAUTIONS

The Material Safety Data Sheet (MSDS) and container labels must be read and understood prior to use.

## MAINTENANCE

Geogard Primer is designed to be top coated with a Tremco Powdered Metals urethane system. It is recommended that the coating installation be checked on a regular schedule with additional inspections after the system has been exposed to severe weather conditions. Small area touch-up can be made at any time by following the recommended application procedures.

## TECHNICAL SERVICE

TREMCO has a team of qualified Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information or service and advice, call Customer Service on (02) 9638 2755 or fax (02) 9638 2955.

## STATEMENT OF POLICY AND RESPONSIBILITY

The Statements provided concerning the materials shown are intended solely as a general guide for material usage and are believed to be true and accurate. Since the manner of use is beyond our control, Tremco DOES NOT MAKE NOR DOES IT AUTHORISE ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE, OR ANY OTHER WARRANTY, GUARANTEE OR REPRESENTATION, EXPRESSED OR IMPLIED, CONCERNING THIS MATERIAL EXCEPT THAT IT CONFORMS TO TREMCO'S PRODUCT SAMPLE. Buyer and user accept the product under those conditions and assume the risk of any failure, injury of person or property and loss or liability resulting from the handling, storage or use of the product, whether or not it is handled, stored, used in accordance with directions or specifications. UNDER NO CIRCUMSTANCES SHALL TREMCO BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES ARISING FROM ANY BREACH OF WARRANTY. IN ALL CASES, TREMCO'S LIABILITY IS LIMITED, AT TREMCO'S OPTION, TO THE REPLACEMENT OF GOODS, OR THEIR VALUE, PROVEN TO BE DEFECTIVE IN MANUFACTURING.