

MULTIFORM

Multiform

Modular Tile

Construction
Tufted, Textured Loop

Tile Size
1 m x 1 m (39.4" x 39.4")
50 cm x 1 m (19.7" x 39.4")
25 cm x 1 m (9.85" x 39.4")

Yarn Type
Milliken-Certified WearOn® Nylon Type
6,6

Stain Repel / Stain Resist / Soil Release
StainSmart®

Antimicrobial
AlphaSan® AF Built-In Protection†

Dye Method
DCP (Digital Color Placement)

Tufted Face Weight
15 oz/yd² (509 g/m²)

Gauge
1/12

Stitches Per Inch
9.8

Tufts
117.6/in² (1,821/100 cm²)

Finished Pile Height
0.13" (3.30 mm)

Finished Pile Thickness
0.08" (2.03 mm)

Average Density (Finished)
6,541

Standard Backing
PVC-Free Underscore™ ES Cushion
Available with TractionBack®

Recycled Content by Total Weight
ES Backing: 39.3% Pre-Consumer,
0.0% Post-Consumer
ESP Backing: 28.6% Pre-Consumer,
10.7% Post-Consumer

Nominal Total Thickness
0.28" (7.1 mm)

Nominal Total Weight
89 oz/yd² (3,024 g/m²)

Flammability (Radiant Panel
ASTM-E-648)
≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or
ASTM-E-662)
≤ 450

Methenamine Pill Test (CPSC FF-1-70
or ASTM D 2859
Self-Extinguishing

Lightfastness (AATCC 16E)
≥ 4.0 at 80 Hours

Crocking (AATCC 165)
≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20%
R.H., 70° F.
≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating
(TARR)

Severe Traffic End-Use Applications

Recommended Maintenance
MilliCare® Textile and Carpet Care
Service Network

Indoor Air Quality—CRI Green Label
Plus™
GLP0793, Carpet Category 5Y

Recommended Installation Method(s)
Monolithic, Planks, Random

WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®)
Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency

Lifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.

ENCRYPTION

Linear Code

Modular Tile

Construction
Tufted, Textured Loop

Tile Size
25 cm x 1 m (9.85" x 39.4")

Yarn Type
Milliken-Certified WearOn® Nylon
Type 6,6

Stain Repel / Stain Resist / Soil
Release
StainSmart®

Antimicrobial
AlphaSan® AF Built-In Protection†

Dye Method
DCP (Digital Color Placement)

Tufted Face Weight
15 oz/yd² (509 g/m²)

Gauge
1/12

Stitches Per Inch
9.8

Tufts
117.6/in² (1,821/100 cm²)

Finished Pile Height
0.13" (3.30 mm)

Finished Pile Thickness
0.08" (2.03 mm)

Average Density (Finished)
6,541

Standard Backing
PVC-Free Underscore™ ES Cushion
Available with TractionBack®

Recycled Content by Total Weight
ES Backing: 39.3% Pre-Consumer,
0.0% Post-Consumer
ESP Backing: 28.6% Pre-Consumer,
10.7% Post-Consumer

Nominal Total Thickness
0.28" (7.1 mm)

Nominal Total Weight
89 oz/yd² (3,024 g/m²)

Flammability (Radiant Panel
ASTM-E-648)
≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or
ASTM-E-662)
≤ 450

Methenamine Pill Test (CPSC FF-1-70
or ASTM D 2859
Self-Extinguishing

Lightfastness (AATCC 16E)
≥ 4.0 at 80 Hours

Crocking (AATCC 165)
≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20%
R.H., 70° F.
≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating
(TARR)
Severe Traffic End-Use Applications

Recommended Maintenance
MilliCare® Textile and Carpet Care
Service Network

Indoor Air Quality—CRI Green Label
Plus™
GLP0793, Carpet Category 5Y

Recommended Installation Method(s)
Planks

WARRANTIES

Lifetime Antimicrobial Protection (AlphaSan®)
Lifetime Face Fiber Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Color Pattern Permanency

Lifetime Floor Release
Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability
Lifetime Tuft Bind
Lifetime Edge Ravel
Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.