

Reference

0299.

**Application** 

Hanging lamps

**Installation type** 

Surface

Description

Wireflow designed by Arik Levy. A hanging lamp which reviews and updates the chandelier look through an exercise of simplification that explores its essence and enhances its outline with great delicacy and at the same time a strong formal presence. Its appearance, as a structure of fine cables finished with eight LED terminals, discretely connects with classic chandelier models, taking this type of lamp to a new, groundbreaking and futuristic dimension. Employing CREA product configurator software, the design can be modified to adapt to your specific project requirements.

Diffuser

Pressed-glass diffuser


Materials Diffuser: Glass Body: Aluminum Rods: Steel Ceiling rose: Steel

Finish



0299-04 Black lacquer (RAL 9005)

Sketch



**Electrical characteristics** 

8 x LED 4,5W 350mA



Total 35.8 W







Led 2700K CRI >80 3922 lm 109 lm/W

Fixture: 1573 lm 60 lm/W

Driver included: CC - Constant Current 350 mA 100-240V 50/60Hz

Electronic dimming DALI 1-10V PUSH

ficha.fichatecnicaproducto.regulacion.opcional SMART

**Physical characteristics** 

2 Box / 0.09 x 1.62 x 1.63 m. / Vol. 0.3245 m<sup>3</sup> / Gross weight 18.2 kg. / Net weight 15.3 kg.

Installation and assembly

Please, see the installation manual

**Light distribution** 

## **General lighting**

Lamp for general lighting that equally distributes the light in all directions.




Photometric data

Efficiency: 40.11% Isolux : Floor  ${\it Coordinate \ system: CG}$ Light position :

Total flux: 3922.20 X=0.00m Y=0.00m Z=2.50m

Maximum value : 53.86 Light position: C=15.00 G=55.00 Symmetry on the planes : Double symmetrical



Certificates











