PROMASTOP®-CC
Fire stopping coating

	PROMASTOP®-CC liquid
Colour	light grey
Consistency	liquid
Density	1.5 ± 0.2 g/cm³
Use category	Class X
Reaction to fire	Class E
VOC Content	0 g/l

General description
PROMASTOP®-CC is a water-based 'hybrid' fire stopping coating. It combines the positive qualities of intumescent and ablative coatings. In the field of fire stopping penetrations, PROMASTOP®-CC provides reliable protection against the spread of smoke, fire and heat due to its foaming effect and simultaneous formation of a hard and solid char.

Field of application
PROMASTOP®-CC is a fire stopping coating for services in walls and floors. It is designed for use with single cables, cable bundles, combustible and non-combustible pipes, fire dampers and also insulated ventilation systems to prevent the spread of smoke, fire and heat. There is also an EN-test for PROMASTOP®-CC to prevent fire from spreading along cables and cable bundles.

System advantage / customer benefit
- Suitable for use in damp rooms (i.e. high humidity levels, splashing water, etc.)
- Excellent adhesive properties
- Minimal section insulation for all cable groups

Test certificate / approval
- EN1366-3/4
- EN13501-1/2
- ETAG 026-2
- EN ISO 10140-2
- EN ISO 717-1
- EN 50266-1-1: 01 and 2-2: 01
- IEC 60331-11: 01 and 21: 01

Packaging
- 12.5 kg plastic buckets
- 44 buckets/palett
- 550 kg/palett

Subject to change

Storage requirements
- Store in cool and dry conditions: 3°C - 35°C
- Shelf life of original sealed containers at least 6 months
- Once opened, containers should be finished swiftly

Safety instructions
- Please refer to the safety data sheet for additional advice