

Bona® DriFast® Sealer

Technical data sheet

A quick drying, polyurethane sanding sealer. Designed to penetrate and seal bare wood. Compatible with all Bona® stains, oil-modified and waterborne finishes.

- Easy application
- Penetrates and seals the wood
- Fast drying – 1 ½ - 2 hours
- Rapid hardness development
- Sands easily for use as a sanding sealer
- Meets ASTM D 1640 for quick-dry sealers
- VOC Compliant under U.S. EPA regulations
- Clean up with mineral spirits

Technical data

Physical Characteristics:

Ingredients – Mineral spirits (solvent), urethane resins, silica, driers.

Color – wet – amber; dry – light amber

Solids – 37%

Density – 7.21 lbs/gallon (0.866 S.G.)

US Regulatory VOC – 550 g/L

Odor – Mineral spirits

Stability – Two year shelf life in unopened container

Flash Point – 103° F (39° C)

Packaging – 1-gallon can, 5-gallon pail

Application Characteristics:

Clarity – Clear

Leveling – Excellent

Defoaming – Excellent/complete

Drying Time – 1-1/2 - 2 hours

Application Tools – Lambswool applicator, synthetic floor coater

Coverage – 600-700 square feet per gallon

Percent Cured After 24 Hours – 60%

Maximum Cure – 2 weeks

Recommended Use

Formulated for use under all Bona® oil-modified and waterborne finishes.

Directions

BEFORE USING, READ ALL DIRECTIONS AND SAFETY DATA SHEETS

FOR TECHNICAL ADVICE: Call Bona US at 800/872-5515

COMPATIBILITY STATEMENT: Bona® DRIFAST® Sealer is designed to penetrate and seal bare wood. It is compatible with all Bona® stains, oil-modified and waterborne finishes. ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY IF USING ANYTHING OTHER THAN A BONA® PRODUCT.

PREPARATION: SANDING AND FINISHING

1. Sand and prepare floor using NOFMA-accepted methods. NOTE: It may be necessary to first trowel-fill the entire floor, depending on the extent of cracks between strip and parquet flooring.
2. Make your final cut with 80-grit paper and screen to 80-100-grit screen. **3.** Vacuum thoroughly.
4. Tack with dry microfiber mop. **5.** Apply sealer and finish system (see finish directions).

APPLICATION: STIR WELL BEFORE USING!

1. After preparing surface, apply DRIFAST® Sealer at 600-700 sq. ft. per gallon with lambswool applicator or synthetic floor coater applicator.
2. Avoid leaving puddles of excessive amounts of sealer on the floor.
3. Allow surface to thoroughly dry (1 1/2 - 2 hours). High humidity and/or low temperature conditions will extend the drying time while increased ventilation and airflow will reduce dry time.
4. Abrade surface thoroughly with a Bona® Conditioning Pad or a used 120-grit screen before finishing.
5. Vacuum thoroughly and tack with mineral spirits.

Finishing 



Bona®

Bona[®] DriFast[®] Sealer

Technical data sheet

6. Apply a Bona[®] oil-modified or waterborne finish.

STORAGE AND DISPOSAL: Keep container closed when not in use. Do not transfer contents to other containers for storage and disposal. Do not return used material to the original container; reapply or dispose of. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

DANGER: RAGS, STEEL WOOL OR WASTE SOAKED WITH DRIFAST[®] SEALER MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. IMMEDIATELY AFTER EACH USE, PLACE RAGS, STEEL WOOL OR WASTE IN A SEALED, WATER-FILLED METAL CONTAINER.

Maintenance

CLEAN-UP: Clean applicator tools and equipment with mineral spirits.

STORAGE AND DISPOSAL: Keep container closed when not in use. Do not transfer contents to other containers for storage and disposal. Do not return used material to the original container; reapply or dispose of. In case of spillage, absorb with inert material. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Order Information

Item #:

Quart: SB750051001

1 Gallon: SB750018172

5 Gallon: SB750018173

#/Case:

Quart: 6

1 Gallon: 4

5 Gallon: 1