



Design K.Begasse




Shape

Surfaced mounted accent lighting

SHAPE creates uniform light on the outer edge of windows producing charming light effects on residential, public, historical and artistic façades. Miniaturization, versatility and high performances are the typical characteristics of this product which is able to illuminate even wide openings with a minimum energy consumption and its high functionality level. The light fitting uses only one LED and its inclination can be easily adjusted according to the different inclinations of window sills keeping in this way its capacity to create attractive light scenes.



reddot award 2014
winner



www.simes.it/shape



House of Fates, Budapest, Hungary - Design FBI Studio © ph. Tamás Bujnovszky / Be light Kft.

SHAPE Surfaced mounted accent lighting

Die-cast EN AB-47100 aluminium (low copper content) housing with high corrosion resistance.
 Protective Cover with clip locking system.
 No visible screws.
 Clear polycarbonate diffuser.
 Luminaire hard wired with single neoprene cable.
 Silicone gaskets.
Double powdered paint.

The fitting allows an adjustment of approximately 5° for the perfect alignment of the light beam with the window frame.

Colours:

- White (code 01)
- Aluminium grey (code 14)

Protection class
 IP65

Isolation class
 CLASS I ⊕ SHAPE
 CLASS III ⚡ MINISHAPE

Mechanical resistance of diffuser
 IK 10

For the latest technical information and product updates with LED technology please refer to the official website (www.simes.it)

REGISTERED DESIGN



S.3424

REMOTE FIXED-POWER SUPPLY
 230V/1200mA
 Power consumption 6W
 Dimensions 57mm x31mm x21mm
IP20

Must be installed in protect area, suitable for 1 device.





S.3423

REMOTE MULTI-POWER SUPPLY
 230V/350mA-1000mA
 Dimmable 1-10V, PUSH BOTTON
 Maximum power consumption:
 at 350mA 15W
 at 1000mA 39W
 Dimensions 130mm x67mm x21mm
IP20

For easy installation we recommend the wiring of maximum 2 devices in series to each power supply.

Mini-Shape



S.6425W □



With led white **3000K** CRI70
 Rated input power 1,0W-350mA ÷ 3,6W-1200mA
 With radial lens 10°x170°
 Requires remote power supply 230V/**350mA-1000mA** (type S.3423)
 or remote power supply 230V/**1200mA** (type S.3424)

S.6425N □

With led white **4000K** CRI70
 Rated input power 1,0W-350mA ÷ 3,6W-1200mA
 With radial lens 10°x170°
 Requires remote power supply 230V/**350mA-1000mA** (type S.3423)
 or remote power supply 230V/**1200mA** (type S.3424)

mA	350	500	700	900	1000	1200
Watt	1,0	1,5	2,1	2,7	2,9	3,6
lumen (3000K)	80	91	102	114	122	151
lumen (4000K)	85	105	125	146	156	200

Shape



S.6420W □

With led white **3000K** CRI70 295lm
 Rated luminaire luminous flux 151lm
 Rated input power 4,7W 240V
 With radial lens 10°x170°

S.6420N □

With led white **4000K** CRI70 428lm
 Rated luminaire luminous flux 200lm
 Rated input power 4,7W 240V
 With radial lens 10°x170°