

Technical data sheet



**ceramica
SANT'AGOSTINO**

Via Statale, 247 44047 S. Agostino (FE) Italy

EN 14411

Marking year: 2017

Rev.: 0 5/10/2017

Product: COLORART CARB.15120

Series: COLORART

Product description and use

Dry-pressed ceramic tiles with group BlaGL
in Through body porcelain
for use in Indoor and outdoor wall and floor tiles

CHARACTERISTICS	PERFORMANCE DECLARATION	NOTES
Reaction to fire	Class A1 and Class A1 fl	Based on decision n. 96/603/CE and its amendments
Bending strenght	Breaking strenght > 1300 N Bending strenght > 35 N/mm**2	Not suitable for ceiling liners
Thermal resistance	Resistant	
Slip degree	NPD BCRA D.M. 236/89 NPD DIN 51130 NPD DIN 51097	In case the National Legislation demands specific requirements, it is necessary to require the relevant performance definition to the producer.
Adhesion resistance	With cement adhesives NPD N/mm**2 With dispersion adhesives NPD N/mm**2 With resin based adhesives NPD N/mm**2 With cement mortar NPD N/mm**2	In case the National Legislation demands specific requirements, it is necessary to require the relevant performance definition to the producer.
Resistance to friction	NPD	In case the National Legislation demands specific requirements, it is necessary to require the relevant performance definition to the producer.
Durability	Frost resistance Resistant	
Dangerous substances yield	Cadmium yield NPD mg/dm**2 Cadmium lead NPD mg/dm**2	In case the National Legislation demands specific requirements, it is necessary to require the relevant performance definition to the producer.

Realizzato con tecnologia SMART FORMS - www.santforms.com