

Overview

The IntelliFlex I/O Contact Closure Interface allows up to 6 contact closure inputs to be connected to the network. These are grouped into 3 sets of Up/Down signals, each of which can control any number of shades on an IntelliFlex I/O network. Configuration is done using the onboard programming buttons, without rewiring or the use of external configuration devices. Power is provided through the IntelliFlex I/O network using a single ethernet cable for power and communication.

Features

- 3 independent groups of Up/Down contacts.
- Flexible control signal options, including full movements to motor limits, manual control to intermediate stops.
- Indoor use only

Compatible Components

Tools	Motor Limit Tool	PN: C202.030
User Input Devices	Single Zone Wall Switch*	PN: C112.161
	Dual Zone Wall Switch*	PN: C112.162
	Handheld Remote	PN: C156.270
Network Devices	Network Device Connector	PN: C156.267
	Wireless Network Gateway	PN: C156.268
	AV Gateway*	PN: C156.269
	Contact Closure Interface*	PN: C156.273
	Sensor/Schedule Interface*	PN: C156.272

*One NDC is included with each of these devices



TECHNICAL SPECIFICATIONS

Material: ABS plastic

Dimensions: 3" x 3" x 1" 76 x 76 x 25mm

Operating Temp: Ambient

Part of the IntelliFlex I/O System

IntelliFlex I/O by Draper is a complete control solution for motorized roller shades. Intelligent motors are connected to wall switches and other input devices through a wired network. This network allows communication between the devices and also distributes power to them from the motors, eliminating the need for external power supplies. Configuration is done from the devices themselves, with no need for a computer connection to the network. Networks can include up to 120 devices and extend to 4000 feet in total with no further restrictions on connections between components.

IntelliFlex I/O System Overview - Contact Closure Interface

