

Overview

The IntelliFlex I/O Wireless Network Gateway allows wireless devices to control shades on the wired network.

Features

- Required to use the handheld remote (Part#C156.270) in a wired network.
- LEDs indicate the status of both the wired and wireless networks
- Allows wireless control of the entire network from a single receiving point

Compatible Components

Tools	Motor Limit Tool	PN: C202.030
User Input Devices	Single Zone Wall Switch*	PN: C112.161
	Dual Zone Wall Switch*	PN: C112.162
	Handheld Remote	PN: C156.270
Network Devices	Network Device Connector	PN: C156.267
	Wireless Network Gateway	PN: C156.268
	AV Gateway*	PN: C156.269
	Contact Closure Interface*	PN: C156.273
	Sensor/Schedule Interface*	PN: C156.272

**One NDC is included with each of these devices*



TECHNICAL SPECIFICATIONS

Material: ABS plastic

Dimensions: 3 3/8" x 2" x 1 1/16" 85 x 52 x 27mm

Operating Temp: Ambient

Shipping Weight: 1 lb 0.45 kg

Approved for use in plenum spaces

Indoor use only

Part of the IntelliFlex I/O System

IntelliFlex I/O by Draper is a complete control solution for motorized roller shades. Intelligent motors are connected to wall switches and other input devices through a wired network. This network allows communication between the devices and also distributes power to them from the motors, eliminating the need for external power supplies. Configuration is done from the devices themselves, with no need for a computer connection to the network. Networks can include up to 120 devices and extend to 4000 feet in total with no further restrictions on connections between components.

IntelliFlex I/O System Overview - Wireless Network Gateway

