




Tonight

Bollard

Tonight is a bollard with an essential design particularly suitable for more urban project applications. It is characterised by a very slim pole head where the glass is positioned horizontally to protect the optical group that is totally hidden from sight.

The opal prismatic glass results in a very uniform light distribution, whilst the milled diffuser absorbs any stray light to reduce glare and assure good visual comfort.

Tonight has been developed in two variants, 180° and 360° light distribution.






TONIGHT Bollard

Extruded EN AW-6060 aluminium profile, Die-cast EN AB-47100 aluminium housing with high corrosion resistance.
 Micro etched prismatic glass diffuser.
 Stainless steel screws.
 Pre-wired luminaire with neoprene cable and connector for connection in the bollard.
 Silicone gaskets.
Double powder paint.

Colour:

● Anthracite grey (code 24)

Protection class
 IP65

Isolation class
 CLASS II 

Mechanical resistance
 IK 06

Leds 4000K CRI90 versions are available on request.
 Integral DALI version available on request with Surcharge.

For the latest technical information and luminaire updates with LED technology please refer to www.simes.it

REGISTERED DESIGN



S.4171



FLANGE FOR TONIGHT Ø 200mm
 Flange to be fixed in concrete with stainless steel screws for fixing in the ground.



S.5506


4 way connector for through wiring (in/out)

180°




S.2110W □

MID-POWER LED **3000K** CRI90 1120lm
 Rated luminaire luminous flux 220lm
 Rated input power 10W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Computer-simulated photometrics



360°



S.2111W □

MID-POWER LED **3000K** CRI90 3360lm
 Rated luminaire luminous flux 660lm
 Rated input power 30W
 220V-240V AC 50/60Hz / DC Not Dimmable
 Computer-simulated photometrics

