# PH 2/1 Pendant


Project name:


Project type:


Notes:




## Light distribution diagrams









### Variant options

Light source	Voltage frequency	Color	Class	Cable type
1/40W/G16.5/IF candelabra	120V	Black metalized	-	BLK
		Brass metalized	II	WHT
		High lustre chrome plated		

#### **Product description**

Suspended glass luminaire. Iconic design. Part of a wide family of multiple sizes.

Can be mounted on 4" octagonal junction box.

#### Design

Poul Henningsen

#### Weight

Min: 2.083 lbs Max: 2.083 lbs

#### Voltage

120V

#### **Light description**

Glare free, symmetric distribution. Glow in mouth-blown glass Downward directed light from glass shades Diffuse light from opal glass shades

#### Mounting

Shades: opal, mouth-blown glass, 2mm (0. 08") thick, sandblasted interior for diffuse light distribution. Stem of high lustre chrome plated aluminum above glass.

Socket: Porcelain, candelabra base for G16. 5, frosted envelope lamps.

Socket position is adjustable to allow correct lamp position and fixture illumination.

Canopy: 5. 3" diameter x 0. 9" tall cone of spun aluminum.

Cable: black PVC coated, 12 ft.

#### **Finish**

Black metalized, Brass metalized, High lustre chrome plated

